






<h2 style="margin: 0;">Datasheet</h2> <h3 style="margin: 0;">0958-1200-2-F</h3>		
SWL	7.3 t	
Pipe OD	9-5/8"	
Maximum weight per pipe	895 kg	
Pipe capacity per system	8	
M20 Bolt length	330mm	
Lifting pole	LP - F	
H-Profile	0958TU-1200	
TL weight per system	135 kg	
<p>CODES AND STANDARDS</p> <ul style="list-style-type: none"> DNVGL-ST-0378 NORSOK R-002 LOLER 1998 Lifting operation and lifting equipment regulations ILO Conversation No. 152 CE declaration of conformity Machinery Directive: MD2006/42/EC 		
<p>TEST</p> <ul style="list-style-type: none"> Load Test 2X SWL on 20% per batch NDT 100% of Primary per batch before and after test 5 yearly load test 		
<p>H-Profile</p> 		<p>Lifting Pole</p> 

Stacking


Sketch	Systems Stacked	Height (mm)	Joints	Supported	Truck	Boat	Rig	Yard
A	1	780	8		X	X	X	X
B	2	1500	16		X	X	X	X
C	3	2220	24		(X)		X	X
D	4	2940	32	X			X	X
E	5	3650	40	X			X	X

(X): Depending on Truck set-up and regulation

All sketch dimensions in mm



Spacing							
Status	w (width) n (number of rows)	S _w (system width)	k(constant)	y(info)	p(info)	T _w (total width)	f(constant)
Storages	$w = S_w + k \cdot (n - 1)$	1074	1146	0	72	$T_w = w + 2f$	72
Running on rig	$w = S_w + k \cdot (n - 1)$	1074	1186	40	112	$T_w = w + 2f$	72



Example: Top view of Systems

Example:
Spacing of 3 systems

$$w = S_w + k \cdot (n - 1) = 1074 + 1146 \cdot (3 - 1) = 3366\text{mm}$$


$$T_w = w + 2f = 3366 + 2 \cdot 72 = 3510\text{mm}$$

The width “w” for spacing of systems is 3366mm from the first pipe to the last and the total width “T_w” is 3510mm between the 2 outer most Lifting Poles

Footprint

The figure below shows the footprint surface area of a single H-profile.

The footprint is shared between the lowest H-profiles based on the number of frames and the number systems stacked



Example: Footprint Surface Area

Maximum Footprint Table (based on 7.3mT SWL)			
System Stacked	2 frames	3 frames	4 frames
1	298,4 kN/m ²	202,5 kN/m ²	170,5 kN/m ²
2	596,8 kN/m ²	405 kN/m ²	341 kN/m ²
3	895,2 kN/m ²	607,4 kN/m ²	511,5 kN/m ²
4	1193,6 kN/m ²	809,2 kN/m ²	682 kN/m ²
5	1492 kN/m ²	1012,4 kN/m ²	852,6 kN/m ²